

Specialty Wholesale Supply
Division of Maki Corporation

Low E coating 7257 change effective April 2017
Energy Star Ratings
Standard Glass Packages
In Reference to ATI Report E7526.09-116-45 on January 18, 2017

Series 4000 & 4500 DuraGard XT Double Hung

Dual Glazed
Neopor Foam in Sash and Head of Frame
Clear SSB/Argon/Low E (7257) 7/8" IG
U-Factor: 0.28
SHGC: .40G/.45NG
VT: .48G/.54NG
CR: 57
Air Infiltration: 0.06 option 23

Tri-Max

Neopor Foam in Sash and Head of Frame
Clear DSB/Argon/Clear SSB/Argon/DSB Low E (7257) 1" IG
U-Factor: 0.23
SHGC: .36G/.40NG
VT: .44G/.49NG
CR: 64
Air Infiltration: 0.06 option 26/27

In Reference to ATI Report E7528.08-116-45 on January 18, 2017

Series 4100 & 4600 DuraGard XT Horizontal Slider

Dual Glazed
Neopor Foam in Sash
Clear SSB/Argon/Low E (7257) 7/8" IG
U-Factor: 0.28
SHGC: .40G/.45NG
VT: .49G/.55NG
CR: 61
Air Infiltration: 0.08 option 14

Tri-Max

Neopor Foam in Sash
Clear DSB/Argon/Clear SSB/Argon/DSB Low E (7257) 1" IG
U-Factor: 0.23
SHGC: .37G/.41NG
VT: .44G/.50NG
CR: 65
Air Infiltration: 0.08 option 17/18

Series 4200 & 4700 DuraGard XT Picture

Dual Glazed
Neopor Foam in Frame
Clear SSB/Argon/Low E (7257) 7/8" IG
U-Factor: 0.25
SHGC: .43G/.48NG
VT: .52G/.58NG
CR: 59
Air Infiltration: 0.02 option 43

Tri-Max

Neopor Foam in Frame
Clear DSB/Argon/Clear SSB/Argon/DSB Low E (7257) 1" IG
U-Factor: 0.20
SHGC: .39G/.44NG
VT: .48G/.52NG
CR: 67
Air Infiltration: 0.02 option 47/48

In Reference to ATI Report E4346.28-116-45 on January 19, 2017

Series 7000 & 7500 Trustgard Casement

Dual Glazed
Neopor Foam in Sash
Clear SSB/Argon/Low E (7257) 7/8" IG
U-Factor: 0.27
SHGC: .35G/.39NG
VT: .42G/.47NG
CR: 64
Air Infiltration: 0.07 option 33

Tri-Max

Neopor Foam in Sash
Clear DSB/Argon/Clear SSB/Argon/DSB Low E (7257) 1" IG
U-Factor: 0.22
SHGC: .32G/.35NG
VT: .38G/.42NG
CR: 68
Air Infiltration: 0.02 option 36/37

In Reference to ATI Report E4348.24-116-45 on January 19, 2017

Series 7100 & 7600 Trustgard Awning

Dual Glazed
Neopor Foam in Sash
Clear SSB/Argon/Low E (7257) 7/8" IG
U-Factor: 0.27
SHGC: .35G/.39NG
VT: .42G/.47NG
CR: 60
Air Infiltration: 0.07 option 27

Tri-Max

Neopor Foam in Sash
Clear DSB/Argon/Clear SSB/Argon/DSB Low E (7257) 1" IG
U-Factor: 0.22
SHGC: .32G/.35NG
VT: .38G/.42NG
CR: 67
Air Infiltration: 0.03 option 36/37

Series 1005 & 1006 Trustgard Patio Door

Dual Glazed
No Foam
Clear SSB/Argon/Low E (7257) 7/8" IG
U-Factor: 0.29
SHGC: .41G/.46NG
VT: .49G/.56NG
CR: 57
Air Infiltration: 0.16 option 3

G: Grid • NG: No Grid • SHGC: Solar Heat Gain Coefficient •
VT: Visible Transmittance • CR: Condensation Resistance